



### Product Specifications

<b>Construction</b>	Cut and Loop
<b>Backing</b>	Standard Back
<b>Dye Method</b>	Solution Dyed
<b>Fiber Type</b>	Solution Dyed PET
<b>Face Weight</b>	26 oz./sy (882 grams/m2)
<b>Pattern Repeat</b>	.50" (w) x .75" (l) approx. (1.27cm x 1.91cm)
<b>Gauge</b>	1/8 (3.15 rows/cm)
<b>Standard Width</b>	12 ft 3.66 m
<b>Standard Adhesive</b>	Commercialon Premium Carpet Adhesive
<b>Standard Warranties</b>	<b>Standard Back</b> <b>Living Spaces</b>


### Special Technologies

<b>ProSept® Antimicrobial</b>	Optional
<b>Sentir® Odor-Blocker</b>	Optional


### Environmental Specifications & Tests

<b>NSF 140:</b>	Gold Certified
<b>Total Recycled Content</b>	0%
<b>Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less than 450 flaming (ASTM E 662)
<b>Static Test</b>	Less than 3 kv (AATCC-134)
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>Pill Test</b>	Yes
<b>Lightfastness</b>	Yes

### Colorways



3355 Shell



3356 Surf



3357 Wave



3358 Sand



3359 Tide



3360 Coast