



Product Specifications

Construction	Patterned Cut and Loop
Backing	PremierBac® Plus
Dye Method	Beck Dyed
Fiber Type	Type 6,6 Nylon
Face Weight	40 oz./sy (1356 grams/m2)
Pile Density	7074 oz./y3 (262.31 kg/m3)
Pattern Repeat	72.00" (w) x 77.00" (l) approx. (182.88cm x 195.58cm)
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	10 stitches/in (3.94 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	PremierBac Plus Commercialon Premium Broadloom Adhesive Commercialon Premium Seam Sealer Type 6,6 Nylon Fiber
Optional Warranties	Endure Plus TitanBac Plus

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	32.7%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



2255 Warm To...



2258 Diffuse




2261 Haze Grey



2262 Neutral De..



2265 Grayscale



3106 Noise



3108 Shutter



3109 Sync



3110 Burst