



Product Specifications

|                            |                                                                                                            |
|----------------------------|------------------------------------------------------------------------------------------------------------|
| <b>Construction</b>        | Patterned Loop                                                                                             |
| <b>Backing</b>             | PremierBac® Plus                                                                                           |
| <b>Dye Method</b>          | Solution Dyed                                                                                              |
| <b>Fiber Type</b>          | Encore® SD Ultima® (with recycled content)                                                                 |
| <b>Face Weight</b>         | 15 oz./sy (509 grams/m2)                                                                                   |
| <b>Pile Density</b>        | 5216 oz./y3 (193.41 kg/m3)                                                                                 |
| <b>Pattern Repeat</b>      | 72.00" (w) x 24.00" (l) approx. (182.88cm x 60.96cm)                                                       |
| <b>Gauge</b>               | 1/12 (4.72 rows/cm)                                                                                        |
| <b>Stitches Per Inch</b>   | 10.17 stitches/in (4.00 stitches/cm)                                                                       |
| <b>Standard Width</b>      | 12 ft 3.66 m                                                                                               |
| <b>Standard Adhesive</b>   | Commercialon Premium Carpet Adhesive                                                                       |
| <b>Standard Warranties</b> | <b>PremierBac Plus</b><br><b>Commercialon Premium Broadloom Adhesive</b><br><b>Encore® SD Ultima Fiber</b> |
| <b>Optional Warranties</b> | <b>Endure Plus</b><br><b>TitanBac Plus</b><br><b>Encore® 100 Fiber</b>                                     |


Special Technologies

|                               |          |
|-------------------------------|----------|
| <b>ProSept® Antimicrobial</b> | Optional |
| <b>ProTex® Soil Release</b>   | Standard |
| <b>Sentir® Odor-Blocker</b>   | Optional |

Environmental Specifications & Tests

|                               |                                    |
|-------------------------------|------------------------------------|
| <b>NSF 140:</b>               | Gold Certified                     |
| <b>Total Recycled Content</b> | 35.02%                             |
| <b>Radiant Panel</b>          | Class 1                            |
| <b>Smoke Density</b>          | Less than 450 flaming (ASTM E 662) |
| <b>Static Test</b>            | Less than 3 kv (AATCC-134)         |
| <b>ADA Compliance</b>         | Compliant For Accessible Routes    |
| <b>Pill Test</b>              | Yes                                |
| <b>Lightfastness</b>          | Yes                                |

Colorways



2717 Authentic




2718 Central




2719 Essential




2720 Fundame...




2722 Innate



2723 Key



2726 Inherent



2728 True