



Product Specifications

Construction	Patterned Loop
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	22 oz./sy (746 grams/m2)
Pattern Repeat	48.00" (w) x 48.00" (l) approx. (121.92cm x 121.92cm)
Gauge	1/12 (4.72 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	PremierBac Plus Commercialon Premium Broadloom Adhesive Commercialon Premium Seam Sealer Encore® SD Ultima Fiber
Optional Warranties	Endure Plus TitanBac Plus Encore® 100 Fiber


Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	50.7%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways




3641 Juniper



3642 Hazelwood



3643 Alpenglow




3644 Hearth




3645 Sandstone



3646 Crisp Air



3647 Blue Spru...



3648 Wild Indigo