



Product Specifications

Construction	Textured Patterned Loop
Backing	PremierBac® Plus
Dye Method	Solution/Yarn Dyed
Fiber Type	Encore® BCF (with recycled content)
Face Weight	28 oz./sy (949 grams/m2)
Pile Density	6857 oz./y3 (254.26 kg/m3)
Pattern Repeat	24.00" (w) x 24.00" (l) approx. (60.96cm x 60.96cm)
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	11.6 stitches/in (4.57 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	PremierBac Plus Commercialon Premium Broadloom Adhesive Commercialon Premium Seam Sealer Encore® BCF (with ColorLoc Plus)
Optional Warranties	Endure Plus TitanBac Plus Encore® 100 Fiber


Special Technologies

Colorloc® Plus	Standard
ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	GLP5055
Total Recycled Content	48.5%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



1995 Norman



1996 Bourne




1997 Skywalker



1998 Stella



1999 Atticus



2000 Powers



2001 Katniss



2002 Scout



2003 Bueller



2005 Shaft



2006 Vader