



**Installation Methods:** Brick, Monolithic, Ashlar, Quarter Turn

Product Specifications

<b>Construction</b>	Textured Patterned Loop
<b>Backing</b>	Advance Modular
<b>Dye Method</b>	Solution/Yarn Dyed
<b>Fiber Type</b>	Encore® BCF (with recycled content)
<b>Face Weight</b>	28 oz./sy (949 grams/m2)
<b>Pile Density</b>	7127 oz./y3 (264.27 kg/m3)
<b>Pattern Repeat</b>	N/A
<b>Gauge</b>	1/12 (4.72 rows/cm)
<b>Stitches Per Inch</b>	12.5 stitches/in (4.92 stitches/cm)
<b>Standard Size</b>	24" x 24" approx. (60.96cm x 60.96cm)
<b>Standard Adhesive</b>	Advance Modular Carpet   Cushion Adhesive
<b>Optional Adhesive</b>	Commercialon Premium Modular Adhesive, TileTabs, Nexus Cushion Modular Adhesive
<b>Standard Warranties</b>	<b>Advance Modular Backing</b> <b>Advance Modular Adhesive</b> <b>Encore® BCF (with ColorLoc Plus)</b>
<b>Optional Warranties</b>	<b>Nexus Modular</b> <b>Nexus Cushion Modular</b> <b>Nexus FC Cushion</b> <b>Commercialon Adhesive for Modular Carpet &amp; LVT</b> <b>Tile Tabs</b> <b>Nexus Cushion Adhesive</b> <b>Encore® 100 Fiber</b>

Special Technologies

<b>Colorloc® Plus</b>	Standard
<b>ProSept® Antimicrobial</b>	Optional
<b>ProTex® Soil Release</b>	Standard
<b>Sentir® Odor-Blocker</b>	Optional

Environmental Specifications & Tests

<b>NSF 140:</b>	Gold Certified
<b>Total Recycled Content</b>	52.6%
<b>Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less than 450 flaming (ASTM E 662)
<b>Static Test</b>	Less than 3 kv (AATCC-134)
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>Pill Test</b>	Yes
<b>Lightfastness</b>	Yes

Colorways



1995 Norman



1996 Bourne



1997 Skywalker



1998 Stella



1999 Atticus



2000 Powers



2001 Katniss



2002 Scout



2003 Bueller



2005 Shaft



2006 Vader