



Product Specifications

Construction	Textured Patterned Loop
Backing	PremierBac® Plus
Dye Method	Solution/Yarn Dyed
Fiber Type	Encore® BCF (with recycled content)
Face Weight	21 oz./sy (712 grams/m2)
Pile Density	5186 oz./y3 (192.30 kg/m3)
Pattern Repeat	72.00" (w) x 77.50" (l) approx. (182.88cm x 196.85cm)
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	9.6 stitches/in (3.78 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	PremierBac Plus Commercialon Premium Broadloom Adhesive Encore® BCF (with ColorLoc Plus)
Optional Warranties	Endure Plus TitanBac Plus Encore® 100 Fiber

Special Technologies

Colorloc® Plus	Standard
ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	33.23%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



2085 Lotus




2086 Bliss



2087 Calm



2088 Harmonic



2089 Tranquil




2090 Remedy



2091 Serene



2092 Clear



2093 Stillwater



2094 Breeze



2095 Escape



2096 Solace



2097 Shadow