



Product Specifications

| | |
|----------------------------|---|
| Construction | Textured Patterned Loop |
| Backing | PremierBac® Plus |
| Dye Method | Solution/Yarn Dyed |
| Fiber Type | Encore® BCF (with recycled content) |
| Face Weight | 21 oz./sy (712 grams/m2) |
| Pile Density | 5186 oz./y3 (192.30 kg/m3) |
| Pattern Repeat | 72.00" (w) x 77.50" (l) approx. (182.88cm x 196.85cm) |
| Gauge | 1/12 (4.72 rows/cm) |
| Stitches Per Inch | 9.6 stitches/in (3.78 stitches/cm) |
| Standard Width | 12 ft 3.66 m |
| Standard Adhesive | Commercialon Premium Carpet Adhesive |
| Standard Warranties | PremierBac Plus Commercialon Premium Broadloom Adhesive Encore® BCF (with ColorLoc Plus) |
| Optional Warranties | Endure Plus TitanBac Plus Encore® 100 Fiber |

Special Technologies

| | |
|-------------------------------|----------|
| Colorloc® Plus | Standard |
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release | Standard |
| Sentir® Odor-Blocker | Optional |


Environmental Specifications & Tests

| | |
|-------------------------------|------------------------------------|
| NSF 140: | Gold Certified |
| Total Recycled Content | 33.23% |
| Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |

Colorways




2085 Lotus




2086 Bliss



2087 Calm



2088 Harmonic



2089 Tranquil




2090 Remedy



2091 Serene



2092 Clear



2093 Stillwater



2094 Breeze



2095 Escape



2096 Solace



2097 Shadow