



Product Specifications

<b>Construction</b>	Textured Patterned Loop
<b>Backing</b>	PremierBac® Plus
<b>Dye Method</b>	Solution/Yarn Dyed
<b>Fiber Type</b>	Encore® BCF (with recycled content)
<b>Face Weight</b>	21 oz./sy (712 grams/m2)
<b>Pile Density</b>	5186 oz./y3 (192.30 kg/m3)
<b>Pattern Repeat</b>	72.00" (w) x 77.50" (l) approx. (182.88cm x 196.85cm)
<b>Gauge</b>	1/12 (4.72 rows/cm)
<b>Stitches Per Inch</b>	9.6 stitches/in (3.78 stitches/cm)
<b>Standard Width</b>	12 ft 3.66 m
<b>Standard Adhesive</b>	Commercialon Premium Carpet Adhesive
<b>Standard Warranties</b>	<b>PremierBac Plus</b> <b>Commercialon Premium Broadloom Adhesive</b> <b>Encore® BCF (with ColorLoc Plus)</b>
<b>Optional Warranties</b>	<b>Endure Plus</b> <b>TitanBac Plus</b> <b>Encore® 100 Fiber</b>

Special Technologies

<b>Colorloc® Plus</b>	Standard
<b>ProSept® Antimicrobial</b>	Optional
<b>ProTex® Soil Release</b>	Standard
<b>Sentir® Odor-Blocker</b>	Optional


Environmental Specifications & Tests

<b>NSF 140:</b>	Gold Certified
<b>Total Recycled Content</b>	50.3%
<b>Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less than 450 flaming (ASTM E 662)
<b>Static Test</b>	Less than 3 kv (AATCC-134)
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>Pill Test</b>	Yes
<b>Lightfastness</b>	Yes

Colorways




2085 Lotus




2086 Bliss



2087 Calm



2088 Harmonic




2089 Tranquil




2090 Remedy



2091 Serene



2092 Clear



2093 Stillwater



2094 Breeze



2095 Escape



2096 Solace



2097 Shadow