



**Installation Methods:** Brick, Monolithic, Ashlar, Quarter Turn

Product Specifications

|                            |   |
|----------------------------|---|
| <b>Construction</b>        | Tip Sheared Patterned Loop  |
| <b>Backing</b>             | Nexus® Modular  |
| <b>Dye Method</b>          | Solution Dyed   |
| <b>Fiber Type</b>          | Encore® SD Ultima® (with recycled content)  |
| <b>Face Weight</b>         | 30 oz./sy (1017 grams/m2)   |
| <b>Pile Density</b>        | 8254 oz./y3 (306.06 kg/m3)  |
| <b>Pattern Repeat</b>      | N/A   |
| <b>Gauge</b>               | 1/12 (4.72 rows/cm)   |
| <b>Stitches Per Inch</b>   | 12.3 stitches/in (4.84 stitches/cm)   |
| <b>Standard Size</b>       | 24" x 24" approx. (60.96cm x 60.96cm)   |
| <b>Standard Adhesive</b>   | Commercialon Premium Modular Adhesive   |
| <b>Optional Adhesive</b>   | TileTabs  |
| <b>Standard Warranties</b> | <b>Nexus Modular<br/>Commercial Adhesive for Modular<br/>Carpet &amp; LVT<br/>Advance Modular Backing<br/>Encore® SD Ultima Fiber</b>   |
| <b>Optional Warranties</b> | <b>Nexus Cushion Modular<br/>Tile Tabs<br/>Nexus Cushion Adhesive<br/>Commercialon High Moisture Adhesive for<br/>Modular Carpet and LVT<br/>Nexus FC Cushion<br/>Encore® 100 Fiber</b> |

Special Technologies

|                               |          |
|-------------------------------|----------|
| <b>ProSept® Antimicrobial</b> | Optional |
| <b>ProTex® Soil Release</b>   | Standard |
| <b>Sentir® Odor-Blocker</b>   | Optional |

Environmental Specifications & Tests

|                               |                                    |
|-------------------------------|------------------------------------|
| <b>NSF 140:</b>               | Gold Certified                     |
| <b>Indoor Air Quality</b>     | GLP9716                            |
| <b>Total Recycled Content</b> | 43.2%                              |
| <b>Radiant Panel</b>          | Class 1                            |
| <b>Smoke Density</b>          | Less than 450 flaming (ASTM E 662) |
| <b>Static Test</b>            | Less than 3 kv (AATCC-134)         |
| <b>ADA Compliance</b>         | Compliant For Accessible Routes    |
| <b>Pill Test</b>              | Yes                                |
| <b>Lightfastness</b>          | Yes                                |

Colorways



3319 Scarlet



3320 Arctic




3321 Ink



3322 Mulberry



3323 Moss



3324 Sapphire