LVT



Installation Methods: Ashlar, Herringbone, 1/3 Drop

Product Specifications

Wear Layer	20 mil
Thickness	3mm
Finish / Coating	Enhanced UV Urethane w/ Ceramic Bead
Pattern Repeat	Random Wood Pattern
Edge Treatment	Bevel
Dimensions:	9" x 48"
Standard Adhesive	Commercialon® LVT Adhesive
Backing Class	Commercial Grade
Commercial Traffic	Heavy Commercial
Standard Warranties	15 Year LVT Commercialon Adhesive for Modular Carpet & LVT

Packaging

Sq.ft. per piece / carton	3 / 39
Weight per piece / carton	3.05 (lbs) / 39.64 (lbs)
Pieces per box	13
Boxes per pallet	52

Special Technologies

Added Antimicrobial	ZPT (Zinc Protective Technology)
---------------------	----------------------------------

Environmental Specifications & Tests

Indoor Air Quality	FloorScore® Certified		
LEED v4	Contributes to IAQ: Low Emitting Materials		
End of Life	100% Recyclable		
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)		
Radiant Panel	Class 1		
ADA Compliance	Compliant For Accessible Routes		
ASTM F2055 (Size and Tole	erance)	Passes	
ASTM F386 (Thickness)		Passes	
ASTM F1914 (Residual Inde	entation)	Passes	

ASTM F137 (Flexibility) Passes ASTM F2199 (Dimensional Stability) Passes **ASTM F925 (Chemical Resistance)** Passes ASTM F1514 (Resistance to Heat) Passes ASTM F1515 (Resistance to Light) Passes Passes ASTM E648 (Critical Radiant Flux) **ASTM E662 (Optical Smoke Density)** Passes ASTM C1028 (Slip Resistance) Passes ASTM F970 (Static Load) Passes

Colorways



1000 Notable



1089 Value



1003 Heirloom



1090 Standards



1008 Paradigm



1091 Rarity



1009 Heritage



1107 Principle



1087 Ideal



1088 Benchmark