



Product Specifications

Construction	Textured Patterned Loop
Backing	PremierBac® Plus
Dye Method	Solution Dyed
Fiber Type	Encore® SD Ultima® (with recycled content)
Face Weight	30 oz./sy (1017 grams/m2)
Pile Density	7024 oz./y3 (260.45 kg/m3)
Pattern Repeat	72.00" (w) x 77.40" (l) approx. (182.88cm x 196.60cm)
Gauge	1/12 (4.72 rows/cm)
Stitches Per Inch	12.3 stitches/in (4.84 stitches/cm)
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	PremierBac Plus Commercialon Premium Broadloom Adhesive Commercialon Premium Seam Sealer Encore® SD Ultima Fiber
Optional Warranties	Endure Plus TitanBac Plus Encore® 100 Fiber


Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	GLP5055
Total Recycled Content	47.9%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



2198 Mason



2200 Potter



2201 Weaver



2202 Woodwor...




2204 Painter



2205 Quilter




2206 Glassblow..



2207 Tailor



2210 Blacksmith



3316 Jeweler



3317 Carver



3318 Metalsmith