



Product Specifications

Construction	Level Loop
Backing	PremierBac® Plus (A)
Dye Method	Solution/Yarn Dyed
Fiber Type	Encore® BCF (with recycled content)
Face Weight	20 oz./sy (678 grams/m2)
Pile Density	7452 oz./y3 (276.32 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	7.83 stitches/in (3.08 stitches/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	PremierBac Plus Encore® BCF (with ColorLoc Plus)
Optional Warranties	Endure Plus TitanBac Plus Encore® 100 Fiber


Special Technologies

Colorloc® Plus	Standard
ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	GLP5055
Total Recycled Content	33.41%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes


Colorways




1807 Jump Right..




1808 Make A M...




1811 Tell A Tale



3408 Call An Old..



7412 Speak You...



8400 Take A Trip



8403 Take A D...