



Product Specifications

Construction	Patterned Cut and Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	Solution Dyed PET
Face Weight	30 oz./sy (1017 grams/m2)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Optional Adhesive	TileTabs
Standard Warranties	Nexus Modular Commercialon Adhesive for Modular Carpet & LVT Living Spaces
Optional Warranties	Nexus Cushion Modular Tile Tabs Nexus Cushion Adhesive Nexus FC Cushion Advance Modular Backing Advance Modular Adhesive

Special Technologies

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	
Total Recycled Content	35.6%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Brick, Monolithic, Ashlar, Quarter Turn

Colorways



3325 Aria



3326 Cue



3327 Mixer



3328 Solo



3329 Stage