



**Installation Methods:** Brick, Monolithic, Ashlar, Quarter Turn

Product Specifications

|                            |   |
|----------------------------|---|
| <b>Construction</b>        | Textured Patterned Loop   |
| <b>Backing</b>             | Advance Modular   |
| <b>Dye Method</b>          | Solution Dyed   |
| <b>Fiber Type</b>          | Encore® SD Ultima® (with recycled content)  |
| <b>Face Weight</b>         | 32 oz./sy (1085 grams/m2)   |
| <b>Pile Density</b>        | 15063 oz./y3 (558.55 kg/m3)   |
| <b>Pattern Repeat</b>      | N/A   |
| <b>Gauge</b>               | 1/10 (3.94 rows/cm)   |
| <b>Stitches Per Inch</b>   | 10 stitches/in (3.94 stitches/cm)   |
| <b>Standard Size</b>       | 24" x 24" approx. (60.96cm x 60.96cm)   |
| <b>Standard Adhesive</b>   | Commercial Premium Modular Adhesive   |
| <b>Optional Adhesive</b>   | TileTabs  |
| <b>Standard Warranties</b> | <b>Nexus Modular Commercial Adhesive for Modular Carpet &amp; LVT Advance Modular Backing Encore® SD Ultima Fiber</b>   |
| <b>Optional Warranties</b> | <b>Nexus Cushion Modular Tile Tabs Nexus Cushion Adhesive Commercial High Moisture Adhesive for Modular Carpet and LVT Nexus FC Cushion Encore® 100 Fiber</b> |


Special Technologies

|                               |          |
|-------------------------------|----------|
| <b>ProSept® Antimicrobial</b> | Optional |
| <b>ProTex® Soil Release</b>   | Standard |
| <b>Sentir® Odor-Blocker</b>   | Optional |

Environmental Specifications & Tests

|                               |                                    |
|-------------------------------|------------------------------------|
| <b>NSF 140:</b>               | Platinum Certified                 |
| <b>Total Recycled Content</b> | 37.88%                             |
| <b>Radiant Panel</b>          | Class 1                            |
| <b>Smoke Density</b>          | Less than 450 flaming (ASTM E 662) |
| <b>Static Test</b>            | Less than 3 kv (AATCC-134)         |
| <b>ADA Compliance</b>         | Compliant For Accessible Routes    |
| <b>Pill Test</b>              | Yes                                |
| <b>Lightfastness</b>          | Yes                                |

Colorways



2959 Limestone



2960 Feldspar




2961 Soapstone



2962 Gneiss



2963 Dolostone



2964 Slate



2965 Quartz




2966 Marble



2967 Shale



2968 Talc



2969 Sandstone