



Installation Methods: Brick, Monolithic, Ashlar, Quarter Turn

Product Specifications

| | |
|----------------------------|---|
| Construction | Textured Patterned Loop |
| Backing | Advance Modular |
| Dye Method | Solution Dyed |
| Fiber Type | Encore® SD Ultima® (with recycled content) |
| Face Weight | 19 oz./sy (644 grams/m2) |
| Pile Density | 5925 oz./y3 (219.70 kg/m3) |
| Pattern Repeat | N/A |
| Gauge | 1/12 (4.72 rows/cm) |
| Stitches Per Inch | 10 stitches/in (3.94 stitches/cm) |
| Standard Size | 24" x 24" approx. (60.96cm x 60.96cm) |
| Standard Adhesive | Advance Modular Carpet Cushion Adhesive |
| Optional Adhesive | Commercialon Premium Modular Adhesive, TileTabs, Nexus Cushion Modular Adhesive |
| Standard Warranties | Advance Modular Backing Advance Modular Adhesive Encore® SD Ultima Fiber |
| Optional Warranties | Nexus Modular Nexus Cushion Modular Nexus FC Cushion Commercialon Adhesive for Modular Carpet & LVT Tile Tabs Nexus Cushion Adhesive Encore® 100 Fiber |

Special Technologies

| | |
|-------------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release | Standard |
| Sentir® Odor-Blocker | Optional |

Environmental Specifications & Tests

| | |
|-------------------------------|------------------------------------|
| NSF 140: | Gold Certified |
| Total Recycled Content | 55.4% |
| Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |

Colorways

