



Product Specifications

| | |
|----------------------------|--|
| Construction | Level Loop |
| Backing | PremierBac® Plus (A) |
| Dye Method | Solution Dyed |
| Fiber Type | Encore® SD Ultima® (with recycled content) |
| Face Weight | 20 oz./sy (678 grams/m ²) |
| Pile Density | 7983 oz./y ³ (296.01 kg/m ³) |
| Pattern Repeat | N/A |
| Gauge | 1/10 (3.94 rows/cm) |
| Stitches Per Inch | 8 stitches/in (3.15 stitches/cm) |
| Standard Width | 12 ft 3.66 m |
| Standard Adhesive | Commercialon Premium Carpet Adhesive |
| Standard Warranties | PremierBac Plus Encore® SD Ultima Fiber |
| Optional Warranties | Endure Plus TitanBac Plus Encore® 100 Fiber |

Special Technologies

| | |
|-------------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release | Standard |
| Sentir® Odor-Blocker | Optional |

Environmental Specifications & Tests

| | |
|-------------------------------|------------------------------------|
| NSF 140: | Gold Certified |
| Indoor Air Quality | GLP5055 |
| Total Recycled Content | 70.3% |
| Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |

Colorways

