



Product Specifications

|                            |   |
|----------------------------|---|
| <b>Construction</b>        | Cut and Loop  |
| <b>Backing</b>             | Woven Synthetic   |
| <b>Dye Method</b>          | Solution Dyed   |
| <b>Fiber Type</b>          | PureColor® Nylon  |
| <b>Face Weight</b>         | 28 oz./sy (949 grams/m2)  |
| <b>Pile Density</b>        | 4295 oz./y3 (159.26 kg/m3)  |
| <b>Pattern Repeat</b>      | N/A   |
| <b>Gauge</b>               | 1/8 (3.15 rows/cm)  |
| <b>Standard Width</b>      | 12 ft 3.66 m  |
| <b>Standard Adhesive</b>   | Commercialon Premium Carpet Adhesive  |
| <b>Standard Warranties</b> | <b>Commercialon Premium Broadloom Adhesive</b><br><b>Commercialon Premium Seam Sealer</b><br><b>Living Spaces</b> |

Special Technologies

|                               |          |
|-------------------------------|----------|
| <b>ProSept® Antimicrobial</b> | Optional |
| <b>Sentir® Odor-Blocker</b>   | Optional |

Environmental Specifications & Tests

|                               |                                    |
|-------------------------------|------------------------------------|
| <b>NSF 140:</b>               | Gold Certified                     |
| <b>Total Recycled Content</b> | 48.5%                              |
| <b>Radiant Panel</b>          | Class 1                            |
| <b>Smoke Density</b>          | Less than 450 flaming (ASTM E 662) |
| <b>Static Test</b>            | Less than 3 kv (AATCC-134)         |
| <b>ADA Compliance</b>         | Compliant For Accessible Routes    |
| <b>Pill Test</b>              | Yes                                |
| <b>Lightfastness</b>          | Yes                                |

Colorways



9779 Canyon




9810 Meadow



9858 Granite



9925 Talus



9930 Slope



9969 Point