



Installation Methods: Ashlar, Herringbone, 1/3 Drop

Product Specifications

Wear Layer	12mil
Thickness	2.5mm
Finish / Coating	Enhanced UV Urethane w/ Ceramic Bead
Pattern Repeat	Random Wood Pattern
Edge Treatment	no
Dimensions:	9" x 48"
Standard Adhesive	Commercialon® LVT Adhesive
Backing Class	Commercial Grade
Commercial Traffic	Light Commercial
Standard Warranties	Commercialon Adhesive for Modular Carpet & LVT

Packaging

Sq.ft. per piece / carton	3 / 48
Weight per piece / carton	2.55 (lbs) / 40.78 (lbs)
Pieces per box	16
Boxes per pallet	52


Special Technologies

Added Antimicrobial	ZPT (Zinc Protective Technology)
----------------------------	----------------------------------


Environmental Specifications & Tests

Indoor Air Quality	FloorScore® Certified
LEED v4	Contributes to IAQ: Low Emitting Materials
End of Life	100% Recyclable
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)
Radiant Panel	Class 1
ADA Compliance	Compliant For Accessible Routes
ASTM F2055 (Size and Tolerance)	Passes
ASTM F386 (Thickness)	Passes
ASTM F1914 (Residual Indentation)	Passes
ASTM F137 (Flexibility)	Passes
ASTM F2199 (Dimensional Stability)	Passes
ASTM F925 (Chemical Resistance)	Passes
ASTM F1514 (Resistance to Heat)	Passes
ASTM F1515 (Resistance to Light)	Passes
ASTM E648 (Critical Radiant Flux)	Passes
ASTM E662 (Optical Smoke Density)	Passes
ASTM C1028 (Slip Resistance)	Passes
ASTM F970 (Static Load)	Passes


Colorways




1000 Notable



1003 Heirloom




1007 Curio



1008 Paradigm



1060 Inheritance



1108 Occupy



1109 Manor



1110 Spread