



### Product Specifications

<b>Construction</b>	Cut Pile
<b>Backing</b>	Woven Synthetic
<b>Dye Method</b>	Solution Dyed
<b>Fiber Type</b>	PureColor® Nylon
<b>Face Weight</b>	30 oz./sy (1017 grams/m2)
<b>Pile Density</b>	3476 oz./y3 (128.89 kg/m3)
<b>Pattern Repeat</b>	N/A
<b>Gauge</b>	1/10 (3.94 rows/cm)
<b>Standard Width</b>	12 ft 3.66 m
<b>Standard Adhesive</b>	Commercialon Premium Carpet Adhesive
<b>Standard Warranties</b>	<b>Commercialon Premium Broadloom Adhesive</b> <b>Commercialon Premium Seam Sealer</b> <b>Living Spaces</b>

### Special Technologies

<b>ProSept® Antimicrobial</b>	Optional
<b>Sentir® Odor-Blocker</b>	Optional

### Environmental Specifications & Tests

<b>NSF 140:</b>	Gold Certified
<b>Total Recycled Content</b>	47.9%
<b>Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less than 450 flaming (ASTM E 662)
<b>Static Test</b>	Less than 3 kv (AATCC-134)
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>Pill Test</b>	Yes
<b>Lightfastness</b>	Yes

### Colorways



9770 Peak



9785 Limestone



9791 Frost



9792 Sky



9925 Plateau



9945 Dome