



Installation Methods: Brick, Monolithic, Ashlar

Product Specifications

Construction	Multi-Level Tip Sheared Loop
Backing	Nexus® Modular
Dye Method	Beck Dyed
Fiber Type	Type 6,6 Nylon
Face Weight	32 oz./sy (1085 grams/m2)
Pile Density	5486 oz./y3 (203.42 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Stitches Per Inch	12.5 stitches/in (4.92 stitches/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercial Premium Modular Adhesive
Optional Adhesive	TileTabs, Advance Modular Carpet Cushion Adhesive, Nexus Cushion Modular Adhesive
Standard Warranties	Nexus Modular Commercial Adhesive for Modular Carpet & LVT Type 6,6 Nylon Fiber
Optional Warranties	Nexus Cushion Modular Nexus FC Cushion Advance Modular Backing Tile Tabs Nexus Cushion Adhesive Advance Modular Adhesive

Special Technologies

ProSept® Antimicrobial	Optional
ProTex® Soil Release	Standard
Sentir® Odor-Blocker	Optional

Environmental Specifications & Tests

NSF 140:	Gold Certified
Indoor Air Quality	GLP9670
Total Recycled Content	34.9%
Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



354 Indigo



356 Mollusk



358 Tahini




359 Clove




360 Chicory




363 Clay




369 Cochineal




900 Mink




901 Fossil



903 Terra



904 Teak



905 Sesame



907 Tea



910 Palm



911 Dill



912 Ore




913 Shale




914 Glacier




915 Wenge




916 Shade



917 Tusk




918 Shitake



919 Truffle



920 Oyster



921 Dusk

www.jjflooringgroup.com