



Product Specifications

<b>Construction</b>	Textured Loop
<b>Backing</b>	Standard Back
<b>Dye Method</b>	Solution Dyed
<b>Fiber Type</b>	Encore® SD Ultima® (with recycled content)
<b>Face Weight</b>	26 oz./sy (882 grams/m2)
<b>Pile Density</b>	5318 oz./y3 (197.19 kg/m3)
<b>Pattern Repeat</b>	N/A
<b>Gauge</b>	1/10 (3.94 rows/cm)
<b>Stitches Per Inch</b>	12.66 stitches/in (4.98 stitches/cm)
<b>Standard Width</b>	12 ft 3.66 m
<b>Standard Adhesive</b>	Commercialon Premium Carpet Adhesive
<b>Standard Warranties</b>	<b>Standard Back</b> <b>Encore® SD Ultima Fiber</b>
<b>Optional Warranties</b>	<b>Endure Plus</b> <b>TitanBac Plus</b> <b>Encore® 100 Fiber</b>

Special Technologies

<b>ProSept® Antimicrobial</b>	Optional
<b>ProTex® Soil Release</b>	Standard
<b>Sentir® Odor-Blocker</b>	Optional

Environmental Specifications & Tests

<b>NSF 140:</b>	N/A Certified
<b>Total Recycled Content</b>	25%
<b>Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less than 450 flaming (ASTM E 662)
<b>Static Test</b>	Less than 3 kv (AATCC-134)
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>Pill Test</b>	Yes
<b>Lightfastness</b>	Yes

Colorways

 SRD13 Crest	 SRD14 Lofty	 SRD46 Rocky	 SRD52 Peak	 SRD53 Spectral	 SRD54 Glacial
 SRD56 Rugged	 SRD58 Apex	 SRD59 Mighty	 SRD73 Cliff	 SRD76 Stony	 SRD77 Brow