



Installation Methods: Parquet, Herringbone, Basketweave, Brick, Monolithic, Ashlar

Product Specifications

| | |
|----------------------------|---|
| Construction | Textured Loop |
| Backing | Nexus® Modular |
| Dye Method | Solution Dyed |
| Fiber Type | Encore® SD Ultima® (with recycled content) |
| Face Weight | 24 oz./sy (814 grams/m2) |
| Pile Density | 9972 oz./y3 (369.77 kg/m3) |
| Pattern Repeat | N/A |
| Gauge | 1/10 (3.94 rows/cm) |
| Stitches Per Inch | 10.66 stitches/in (4.20 stitches/cm) |
| Standard Size | 18" x 36" approx. (45.72cm x 91.44cm) |
| Standard Adhesive | Commercialon Premium Modular Adhesive |
| Optional Adhesive | TileTabs, Advance Modular Carpet Cushion Adhesive, Nexus Cushion Modular Adhesive |
| Standard Warranties | Nexus Modular Commercialon Adhesive for Modular Carpet & LVT Encore® SD Ultima Fiber |
| Optional Warranties | Nexus Cushion Modular Nexus FC Cushion Advance Modular Backing Tile Tabs Nexus Cushion Adhesive Advance Modular Adhesive Encore® 100 Fiber |

Special Technologies

| | |
|-------------------------------|----------|
| ProSept® Antimicrobial | Optional |
| ProTex® Soil Release | Standard |
| Sentir® Odor-Blocker | Optional |

Environmental Specifications & Tests

| | |
|-------------------------------|------------------------------------|
| NSF 140: | Gold Certified |
| Indoor Air Quality | GLP9716 |
| Total Recycled Content | 44.4% |
| Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |

Colorways



3361 Breeze



3362 Westerlies



3363 Local



3364 Trade



3365 Winds



3366 Planetary



3367 Monsoon