

# Purfix UltraTech Adhesive

## WARRANTIES

Purfix UltraTech Adhesive is warranted against product failure for the 15 year warranty period of the installation of Bio-Based Resilient Flooring.

We warrant that Purfix UltraTech Adhesive will bond J+J's Bio-Based Resilient Flooring to the properly prepared substrate. This warranty is contingent upon strict adherence to proper adhesive application, transfer and spread rates, and substrates conforming to specified moisture and alkalinity thresholds.

In the event our Purfix UltraTech Adhesive fails to perform to specified standards, we must be notified in writing within seven calendar days of indication of failure. Included with that notification must be a copy of the invoice for the Purfix UltraTech Adhesive. Approved personnel will then inspect the installation.

Should it be determined from the inspection that our Purfix UltraTech Adhesive failed to perform as warranted above, we will resolve the deficiency at our discretion by one or more of the following methods at no charge for materials, freight, and labor:

A) refund the full purchase price of the Adhesive and Flooring product in the affected area, B) repair the affected area, or C) replace the affected area. Areas must be cleared at the customer's expense of all equipment, furnishings, partitions, and similar materials that may have been placed over the Bio-Based Resilient Flooring subsequent to completion of the original installation. We are not responsible for damages caused by the improper use of this adhesive or failure to comply with the instructions accompanying this product.

## EXCLUSIONS

This warranty is assigned to the original purchaser for the Bio-Based Resilient Flooring installed in its original location, and this warranty is non-transferable. Flooding voids all warranties.

- 1) Maximum RH of concrete 95%. RH testing is required. Subfloor temperature must be at least 65°F.
- 2) PH readings for installation should be 7-12 using pH testing strips.